

TECHNICAL CHARACTERISTICS

ARBOR ALFAPRIME 15W-40

PRODUCT CODE: 3637

APPLICATION

Low SAPS lubricant for the new generation low emission engines for tractors, other farming and earthmoving machines, including those equipped with with exhaust gas re-circulation or after treatment systems (EGR, SCR, diesel particulate filter DPF). Suitable for engines with traditional older technology.

SPECIFICATIONS

SAE 15W-40, ACEA E7/E9, API CJ-4, Caterpillar ECF-3 / ECF-2 / ECF-1a, CUMMINS CES 20081, DETROIT DIESEL 93K218, DEUTZ DQC III-10-LA, MACK EO-O PREMIUM PLUS-07, MAN M3575, MB-Approval 228.31, RENAULT RVI RLD-3

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	C & B
DENSITY 15°C	ASTM D 4052	g/cm ³	0,878
VISCOSITY @ 100°C	ASTM D 445	cSt	15.4
VISCOSITEITINDEX	ASTM D 2270	--	135
T.B.N.	ASTM D 2896	mg KOH/g	9.1
FLASH POINT CI. O. C.	ASTM D 92	°C	>200
POUR POINT	ASTM D 97	°C	<-27
FOAM @ 24°C	ASTM D 892	cc/s	0 / 0

All technical data is provided for reference only.