

CARACTERISTICI TEHNICE

TUTELA TRANSMISSION FE-GEAR

CODUL PRODUSULUI: 2313

APLICARE

Synthetic lubricant for manual and automated gearboxes with standard and carbon synchronizers; fuel economy characteristics; for heavy duty commercial vehicles with or without Intarder; oil drain interval up to 300.000 Km.

SPECIFICAȚII

SAE 75W-80, API GL 4, IVECO 18-1807 CLASS MGS1, CONTRACTUAL TECHNICAL REF. N°1112.F11, ZF TE-ML 01L,02L,16K, MAN 341 Type E3, MAN 341 Type Z4

DESCRIEREA TESTULUI

DESCRIEREA TESTULUI	METODĂ	UNITATE	VALOARE TIPICĂ
ASPECT	--	--	BRIGHT
DENSITATE 15°C	ASTM D 4052	g/cm ³	0,860
VÂSCOZITATE @ 100°C	ASTM D 445	cSt	9,65
INDICE DE VÂSCOZITATE	ASTM D 2270	--	153
VÂSCOZITATE @ -40°C	ASTM D 2983	cPs	95000
PUNCT DE INFLAMABILITATE CI. O. C.	ASTM D 92	°C	230
TEMPERATURĂ DE CONGELARE	ASTM D 97	°C	-42

Toate datele tehnice au numai rol de referință.